

AUTOMATIC CLEAN AGENT GAS



Clean Agent Gas (Halon replacement) Automatic Fire Extinguishers are ideal to protect and combat fires in the engine compartments such as in boat or large vehicle.

R- 236 Clean agent automatic extinguishers are a very good choice to protect computer rooms, high value assets or other delicate instrument from fire, as they leave behind no harmful residue. Only one unit should be installed in any one compartment in order to provide the total protection required for that area. The unit required is determined by the gross volume of that compartment.



- ★ Manufactured in the UK.
- ★ Clean Agent Gas: Ozone friendly Halon replacement. Leaves no residue.
- ★ Safe for use on live electrical fires.
- ★ Stored pressure.
- ★ Supplied with powder coated metal transport bracket.
- ★ Brass valve with easy to read pressure gauge.
- ★ Fully compliant with the European Pressure Equipment Directive.
- ★ 5 Year manufacturer's warranty.



Technical Specifications	FX4000GA	FX6000GA
Capacity	4Kg	6Kg
Extinguishing medium	Clean Agent Gas R-236	Clean Agent Gas R-236
Maximum area protected	6.8m ³	10.2m ³
Pressurising gas & pressure	Nitrogen 12 Bar @ 20°C	Nitrogen 12 Bar @ 20°C
Discharge Time	Under 15 seconds	Under 25 seconds
Operating Temperature	79°C +/- 5°C	79°C +/- 5°C
Cylinder material	Steel	Steel
Cylinder weight	2.1 Kg	2.1 Kg
Extinguisher height & Cylinder diameter	330mm - 280mm	330mm - 280mm
Gross weight	7.1Kg	9.1Kg
Test Pressure	29 Bar	29 Bar
Storage temperature	-30°C to +60°C	-30°C to +60°C
Carton size (cm) & weight	28.5 x 28.5 x 36 - 7.7 Kg	28.5 x 28.5 x 36 - 9.7 Kg