






COBAGRiP® Stair Nosing

Increase stair safety with highly visible anti-slip stair nosing

- Durable and easy to install on both existing and new-build steps.
- A hard wearing, gritty surface available in bright colours helps protect against slips and trips whilst meeting the Equality Act requirements (DDA).
- Manufactured with chamfered back edge for additional safety.



**Fire and Safety
Centre**

Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 **Web:** www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk

Parts

Part Number	Size	Colour	Weight (kg)
GRP010001N	3 m x 55 mm x 55 mm	Black	1.8
GRP010002N	2 m x 55 mm x 55 mm	Black	1.2
GRP010003N	1.5 m x 55 mm x 55 mm	Black	0.9
GRP010004N	1 m x 55 mm x 55 mm	Black	0.6
GRP010005N	0.75 m x 55 mm x 55 mm	Black	0.45
Part Number	Size	Colour	Weight (kg)
GRP010701N	3 m x 55 mm x 55 mm	Black/Yellow	1.8
GRP010702N	2 m x 55 mm x 55 mm	Black/Yellow	1.2
GRP010703N	1.5 m x 55 mm x 55 mm	Black/Yellow	0.9
GRP010704N	1 m x 55 mm x 55 mm	Black/Yellow	0.6
GRP010705N	0.75 m x 55 mm x 55 mm	Black/Yellow	0.45
GRP070001N	3 m x 55 mm x 55 mm	Yellow	1.8
GRP070002N	2 m x 55 mm x 55 mm	Yellow	1.2
GRP070003N	1.5 m x 55 mm x 55 mm	Yellow	0.9
GRP070004N	1 m x 55 mm x 55 mm	Yellow	0.6

Technical Specifications

Material	GRP
Product Height	5 mm
Min. Operating Temperature	-50°C
Max. Operating Temperature	+90°C
Environmental Resistance	Suitable for indoor and outdoor environments
Typical Applications	External steps
Installation Method	Bond or screw to surface
Cleaning Method	COBAGRiP should be almost maintenance free in most outside environments. Natural elements will have the effect of cleaning COBAGRiP. Brushing and flushing with a mild detergent solution may be desirable now and again to restore appearance.
Fire Tested to	DIN 13501: Bfl - s1 (2018) & EN ISO 11925-2:2020 & EN ISO 9239-1:2010 (both 2021)
COO (Country of Origin)	CN
Slip Tested to	DIN 51130 - R13 & BS 7976-2 - low slip potential

Additional Information

 Installation Guide	 COBAGRiP EN ISO11925 2 2020 Reaction to Fire
 COBAGRiP EN ISO9239 1 2010 Reaction to Fire	 COBAGRiP Fire Test EN13501 1 2018
 COBAGRiP Pendulum Slip Test BS 7676	 COBAGRiP Ramp Slip Test DIN 51130



**Fire and Safety
Centre**

Available From:

Fire and Safety Centre
15 Atkinsons Way, Foxhills Industrial Estate
Scunthorpe, North Lincolnshire, DN15 8QJ
Tel: 01724 281044 **Web:** www.fireandsafetycentre.co.uk
Email: sales@fireandsafetycentre.co.uk