

FIRECHIEF AUTOMATIC POWDER EXTINGUISHERS

FIRECHIEF®
making the world a safer place

MODEL:

**APS1
APS2
APS6
APS10
APS12
APS1/S
APS2/S**



APS1/S

APS2/S



APS12



APS10



APS6



APS2



APS1

- Designed for use in enclosed areas i.e. engine/plant rooms, switch rooms etc
- Fitted with pressure gauge for easy routine checking
- Stored pressure
- Fixing brackets included with extinguishers
- Supplied with 68°C red bulb
- 2 year guarantee



**Fire and Safety
Centre**

Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 Web: www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk

FIRECHIEF AUTOMATIC POWDER EXTINGUISHERS

FIRECHIEF®
making the world a safer place

The Firechief Automatic Powder Fire Extinguishers are designed for enclosed areas such as engine/plant rooms etc.

Containing ABC dry powder extinguishant which covers most fires involving wood/paper, flammable liquids and electrical fires. The heat-sensitive glass bulb bursts when the temperature rises to 68°C.

MODEL:

**APS1
APS2
APS6
APS10**

**APS12
APS1/S
APS2/S**



Specifications

Model	APS1	APS2	APS6	APS10	APS12	APS1/S	APS2/S
Product Code	100-1004	100-1008	100-1010	100-1006	100-1007	100-1588	100-1589
Description	Firechief 1kg ABC Dry Powder Automatic Extinguisher	Firechief 2kg ABC Dry Powder Automatic Extinguisher	Firechief 6kg ABC Dry Powder Automatic Extinguisher	Firechief 10kg ABC Dry Powder Automatic Extinguisher	Firechief 12kg ABC Dry Powder Automatic Extinguisher	Firechief 1kg ABC Dry Powder Automatic Extinguisher - Slimline	Firechief 2kg ABC Dry Powder Automatic Extinguisher - Slimline
Capacity (kg)	1	2	6	10	12	1	2
Fire Rating	n/a	n/a	n/a	n/a	n/a	n/a	n/a
MED Approval	NO	NO	NO	NO	NO	NO	NO
Coverage (m ²)	1	2	6	10	12	1	2
Recommended mounting height above risk (m)	1.5	1.5	2	2	2	1.5	1.5
Working Pressure (bar)	15	15	15	15	15	15	15
Temperature Range (°C)	(-30°C-+60°C)	(-30°C-+60°C)	(-30°C-+60°C)	(-30°C-+60°C)	(-30°C-+60°C)	(-30°C-+60°C)	(-30°C-+60°C)
Bulb release temp (°C)	68	68	68	68	68	68	68
Product Height (mm)	90	123	180	215	275	327	383
Product Diameter (mm)	160	190	250	270	270	85	110
Filled Weight (kg)	2.2	5.5	8.2	14	16.1	2.2	5.5
Carton Height (mm)	270	270	360	425	465	350	425
Carton Length (mm)	170	190	260	275	275	100	390
Carton Width (mm)	170	190	260	275	275	100	260
Packaged Weight (kg)	2.5	5.8	8.5	14.4	16.4	2.4	5.8
Product EAN	5055377901561	5055377901578	5055377901585	5055377901592	5055377901608	5055377961022	5055377961039

*Guidance coverage likely achieved using recommended mounting height.



**Fire and Safety
Centre**

Available From:

Fire and Safety Centre
15 Atkinsons Way, Foxhills Industrial Estate
Scunthorpe, North Lincolnshire, DN15 8QJ
Tel: 01724 281044 **Web:** www.fireandsafetycentre.co.uk
Email: sales@fireandsafetycentre.co.uk