

CORE RANGE

FIRECHIEF®
making the world a safer place

FIRECHIEF® CTX WATER+ ADDITIVE EXTINGUISHERS

MODEL:

FWA2
FWA9-L CTX

- 35kV dielectric test
- Squeeze grip operation
- Water spray nozzle
- Corrosion resistant finish
- 5 year guarantee




LITHIUM-ION
Suitable for use on lithium-ion battery fires



FWA9-L
100-1704



FWA2
100-1706



**fire
& safety
centre**

Available From:

Fire and Safety Centre
15 Atkinsons Way, Foxhills Industrial Estate
Scunthorpe, North Lincolnshire, DN15 8QJ
Tel: 01724 281044 Web: www.fireandsafetycentre.co.uk
Email: sales@fireandsafetycentre.co.uk

FIRECHIEF® CTX WATER EXTINGUISHERS



Our CTX Water+ Additive extinguishers offer exceptional A class performance as standard. Additionally our 9L FWA9-L has the added benefit of suitability for lithium-ion battery fires, having successfully passed the LiB NTA 8133 test.

MODEL:
FWA2
FWA9-L CTX



Specifications

| Model | FWA2 | FWA9-L |
|------------------------|---|---|
| Product Code | 100-1706 | 100-1704 |
| Description | Firechief 2L Water+ Additive Extinguisher | Firechief 9L Water+ Additive Extinguisher |
| Capacity (l) | 2 | 9 |
| Fire Rating | 13A | 21A |
| Throw Range (m) | ≥3 | ≥4 |
| Discharge Time (secs) | 14 | 50 |
| Working Pressure (bar) | 10 | 10 |
| Temperature Range (°C) | +5 to +60 | +5 to +60 |
| Filled Weight (kg) | 3.8 | 13.8 |
| Product Height (mm) | 400 | 610 |
| Product Diameter (mm) | 110 | 180 |
| Carton Height (mm) | 405 | 615 |
| Carton Length (mm) | 120 | 200 |
| Carton Width (mm) | 120 | 190 |
| Packaged Weight (kg)** | 4.16 | 14.29 |
| Product EAN | 5055377966041 | 5055377965938 |

* Extinguisher, contents and plastic base only (where applicable) - not including hose, bracket or packaging.

** Includes all packaging, hose / horn and bracket.



**fire
& safety
centre**

Available From:

Fire and Safety Centre
15 Atkinsons Way, Foxhills Industrial Estate
Scunthorpe, North Lincolnshire, DN15 8QJ
Tel: 01724 281044 Web: www.fireandsafetycentre.co.uk
Email: sales@fireandsafetycentre.co.uk