

FIRECHIEF® CTX WATER EXTINGUISHER

FIRECHIEF®

making the world a safer place

MODEL:

CXW6 CTX

- Kitemark certified to BS EN 3
- 5 year guarantee
- 35kV dielectric test
- Squeeze grip operation
- Internal polyethylene lining
- Water spray nozzle
- Corrosion resistant finish













100-1619





Available From:

Fire and Safety Centre 15 Atkinsons Way, Foxhills Industrial Estate Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 Web: www.fireandsafetycentre.co.uk

FIRECHIEF® CTX WATER EXTINGUISHER



The Firechief® CTX Water Extinguisher is recognised and trusted by resellers and end users alike.

Tested and approved in the UK for use on class A fires. This extinguisher carries Kitemark certification to BS EN 3.

MODEL:











Specifications

Madal	CVM	CVMO
Model	CXW6	CXW9
Product Code	100-1619	100-1620
Description	Firechief® CTX 6L Water Extinguisher	Firechief® CTX 9L Water Extinguisher
Capacity (I)	6	9
Fire Rating	13A	21A
Discharge Time (secs)	≥9s	≥9s
Working Pressure (bar)	12	12
Temperature Range (°C)	+5 to +60	+5 to +60
Product Height (mm)	535	600
Product Diameter (mm)	162	184
Filled Weight (kg)*	9.3	13.7
Carton Height (mm)	570	620
Carton Length (mm)	175	195
Carton Width (mm)	170	190
Packaged Weight (kg)**	10	14.5
Product EAN	5055377962845	5055377962852

^{*} Extinguisher, contents and plastic base only (where applicable) - not including hose, bracket or packaging.



Tel: 01724 281044 **Web:** www.fireandsafetycentre.co.uk

^{**} Includes all packaging, hose / horn and bracket.



FIRECHIEF® CTX STEEL ALLOY CO2 **EXTINGUISHERS**





making the world a safer place

MODEL:

CXC2S CTX

- Kitemarked approved to BS EN3
- 5 year guarantee
- Lightweight steel alloy construction
- Squeeze grip operation
- Harmless to machinery
- Complete with bracket
- Corrosion resistant finish
- CXC2S supplied with frost free horn







CXC5S 100-1681





FIRECHI

CXC2S 100-1680



Available From:

Fire and Safety Centre 15 Atkinsons Way, Foxhills Industrial Estate Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 Web: www.fireandsafetycentre.co.uk

FIRECHIEF® CTX STEEL ALLOY CO2 EXTINGUISHERS



These lightweight steel alloy CO2 extinguishers are suitable for situations involving flammable liquids and electrical hazards. The CO2 extinguishant is harmless to delicate equipment and materials making it ideal for office environments and for electrical risks where oils, spirits etc are in use.

MODEL:

CXC2S CTX

CO2 fire extinguishers should be standard issue for premises with live electrical fire risk, such as:







Shops





Schools

Hospitals





Specifications

Model	CXC2S	CXC5S
Product Code	100-1680	100-1681
Description	Firechief® CTX 2kg CO2 Extinguisher - Steel	Firechief® CTX 5kg CO2 Extinguisher - Steel
Capacity (kg)	2	5
Fire Rating	34B	89B
Throw Range (m)	≥5	≥5
Discharge Time (secs)	≥6	≥9
Working Pressure (bar)	60±5	60±5
Temperature Range (°C)	-30°C-+60°C	-30°C-+60°C
Product Height (mm)	575	750
Product Diameter (mm)	104	136
Filled Weight (kg)*	6.5	14
Carton Height (mm)	575	750
Carton Length (mm)	180	288
Carton Width (mm)	175	250
Packaged Weight (kg)**	6.9	14.5
Pallet Quantity	84	40
Product EAN	5055377964146	5055377964153

^{*} Extinguisher, contents and plastic base only (where applicable) - not including hose, bracket or packaging.



Available From:

Fire and Safety Centre 15 Atkinsons Way, Foxhills Industrial Estate Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 Web: www.fireandsafetycentre.co.uk

^{**} Includes all packaging, hose / horn and bracket.