



Unimat

Heavy-duty anti-fatigue matting for wet areas



- Versatile rubber runner.
- Open holes provide excellent drainage.
- A real asset in helping to prevent slipping in wet areas.
- Easy to roll up and move to new locations or for cleaning.
- Slip tested to DIN 51130.



**Fire and Safety
Centre**

Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 **Web:** www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk

Parts

| Part Number | Size | Colour | Weight (kg) |
|-------------|------------|--------|-------------|
| UM010001 | 1 m x 5 m | Black | 37 |
| UM010002 | 1 m x 10 m | Black | 74 |

Technical Specifications

| | |
|--|--|
| Material | Rubber mix, including >50% recycled material. |
| Surface Finish | Raised anti-slip textured surface with holes to allow drainage |
| Product Height | 10 mm |
| Product Weight | 4 kg |
| Roll Length | 10 m |
| Min. Operating Temperature | -20°C |
| Max. Operating Temperature | +130°C |
| Resistance to Chemicals | Resistant to water and most mild acids |
| Environmental Resistance | Suitable for wet and dry indoor environments |
| Typical Applications | General industrial, Bars, Catering environments |
| Installation Method | Loose lay |
| Cleaning Method | Hose down or pressure wash using a mild detergent |
| Other Product Performance Information | Impact resistant up to 3 kg /c m ² |
| COO (Country of Origin) | IN |
| Tensile Strength | 3 to 3.5 MPa |
| Slip Tested to | DIN 51130 - R10 |

Additional Information



Unimat - Ramp Slip Test DIN 51130



**Fire and Safety
Centre**

Available From:

Fire and Safety Centre

15 Atkinsons Way, Foxhills Industrial Estate

Scunthorpe, North Lincolnshire, DN15 8QJ

Tel: 01724 281044 **Web:** www.fireandsafetycentre.co.uk

Email: sales@fireandsafetycentre.co.uk